

## Rodamiento conico

### HH506348-HH506310-TIMKEN - HH506348-HH506310-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/hh506348-hh506310-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings					Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> K	Static C <sub>2</sub>	Inner	Outer
mm	mm	mm	N		N		N		
49.212	114.300	44.450	246000	3.60	63700	1.45	29000	HH506348	HH506310
1.9375	4.5000	1.7500	55300		14200		83100		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	A <sub>3</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
44.450	36.980	-13.5	3.5	61.8	71.8	3.3	107.8	87.8	2.7	3.3	72.0	15.6	0.1078	2.36
1.7500	1.4520	-0.53	0.14	2.40	2.85	0.13	4.21	3.42	0.10	0.13			4.97	

## CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952315515
Diámetro interior	49.212 mm
Diámetro exterior	114.3 mm
Espesor	44.45 mm
Invasado	1
Estándar	Ninguna norma

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE