


## Rodamiento conico

### L305648-L305610-TIMKEN - L305648-L305610-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/l305648-l305610-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> C <sub>2e</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
49.987	80.962	18.258	42000	0.30	13000	9500	1.64	L305648	L305610	
1.9690	3.1875	0.7188	13700		3640	2760				

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B		ER. Dr. a <sup>(1)</sup>	Shaft		Housing		Cage		G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
mm	mm	mm	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>				kg		
18.258	14.286	-2.5	1.5	55.8	57.8	1.5	77.0	79.0	8.2	2.8	35.9	20.8	0.9841	0.36
0.7188	0.5625	-0.10	0.06	2.17	2.24	0.06	3.03	2.87	0.01	0.09				0.79

## CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952315577
Diámetro interior	49.987 mm
Diámetro exterior	80.962 mm
Espesor	18.258 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE