


Rodamiento conico 744A-742-TIMKEN - 744A-742-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/744a-742-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂	Static C ₃	Inner	Outer		
mm	mm	mm	N		N		N				
69.850	150.889	44.450	219000	0.33	1.04	62000	40000	1.80	417000	744A	742
2.7500	5.9000	1.7500	71400		18500	10300			52600		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R ⁽¹⁾	Backing Shoulder Dia. d ₁	Backing Shoulder Dia. d ₂	Max Housing Fillet Radius r ⁽¹⁾	Backing Shoulder Dia. D ₁	Backing Shoulder Dia. D ₂	Cage A ₁ ⁽¹⁾	Cage A ₂ ⁽¹⁾	G ₁	G ₂		C ₁
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg
46.632	95.932	-11.8	5.8	82.8	91.8	3.3	142.8	134.0	1.8	1.3	153.6	26.3	0.0089	3.81
1.8325	3.7725	-0.47	0.23	3.23	3.58	0.13	5.59	5.28	0.07	0.05				8.60

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952320748
Diámetro interior	69.85 mm
Diámetro exterior	150.089 mm
Espesor	44.45 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE