


Rodamiento conico 6460-6420-TIMKEN - 6460-6420-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/6460-6420-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂	Static C ₃	Inner	Outer	
mm	mm	mm	N		N		N			
73.025	149.225	53.975	41100	0.28	10700	0.04	40300	6460	6420	
2.6750	5.8750	2.1250	5240		2400		10400			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R ⁽¹⁾	Backing Shoulder Dia. d ₁	Backing Shoulder Dia. d ₂	Max Housing Fillet Radius r ⁽¹⁾	Backing Shoulder Dia. D ₁	Backing Shoulder Dia. D ₂	Cage A ₁ ⁽¹⁾	Cage A ₂ ⁽¹⁾	G ₁	G ₂		C ₃
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg
54.225	64.400	-15.8	3.5	87.8	83.8	3.3	140.8	120.8	2.7	8.7	158.3	20.1	0.0021	4.40
2.1250	1.7500	-0.58	0.14	3.43	3.38	0.13	5.51	5.08	0.10	0.03				9.71

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952321240
Diámetro interior	73.025 mm
Diámetro exterior	149.225 mm
Espesor	53.975 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE