


Rodamiento conico 750A-742-TIMKEN - 750A-742-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/750a-742-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings					Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂	Static C ₃	Inner	Outer
mm	mm	mm	N		N		N		
82.550	150.089	44.450	37900	0.33	67000	0.44	417000	750A	742
3.2500	5.9050	1.7500	84700		21900		53600		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R _{f1}	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ₁ ⁽²⁾	Backing Shoulder Dia. D _s	Cage A ₁ ⁽³⁾	Cage A ₂ ⁽³⁾	G ₁	G ₂	C ₁			
mm	mm	mm	mm	mm	mm	mm	mm	mm				kg		
46.672	36.932	-11.9	0.5	103.6	106.6	3.3	142.8	134.0	1.8	1.3	158.6	26.3	0.9888	3.33
1.8375	1.4575	-0.47	0.20	3.88	4.17	0.13	5.59	5.28	0.07	0.05			7.33	

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952322469
Diámetro interior	82.55 mm
Diámetro exterior	150.089 mm
Espesor	44.45 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE