


## Rodamiento conico 594-592A-TIMKEN - 594-592A-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/594-592a-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
95.250	152.400	39.688	216000	1.36	90000	42000	1.32	219000	594	
3.7500	6.0000	1.5625	48000		12600	9530		71600	592A	

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>1</sub> <sup>(2)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>1</sub>	Cage A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>	A <sub>3</sub> <sup>(3)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
39.688	39.902	-3.5	3.5	194.0	110.0	3.3	144.0	130.0	4.1	1.3	151.4	30.3	0.1410	2.48
1.4500	1.5875	-0.10	0.14	4.00	4.33	0.13	5.67	5.21	0.16	0.07			5.47	

### CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952323725
Diámetro interior	95.25 mm
Diámetro exterior	152.4 mm
Espesor	39.688 mm
Peso	2480 g
Envasado	1
Estándar	Ninguna norma

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE