


Rodamiento conico

M241543-M241510-TIMKEN - M241543-M241510-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/m241543-m241510-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C _{2e}	Factor ⁽²⁾ K	Static C ₂	Inner	Outer	
mm	mm	mm	N		N		N			
200.025	292.100	57.945	600000	3.33	150000	1.78	1170000	M241543	M241510	
7.6790	11.5000	2.2613	130000		35000		263000			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R _{f1}	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ₁ ⁽²⁾	Backing Shoulder Dia. D _s	Cage A ₁ ⁽³⁾	A ₂ ⁽³⁾	G ₁	G ₂	C ₃	kg		
mm	mm	mm	mm	mm	mm	mm	mm	mm						
57.945	46.698	-4.8	3.5	215.0	215.0	3.3	279.0	272.0	4.7	2.8	0.541	127.9	0.1279	12.81
2.2613	1.8125	-0.19	0.14	8.46	8.62	0.13	10.98	10.71	0.18	0.08				27.58

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952327006
Diámetro interior	200.025 mm
Diámetro exterior	292.1 mm
Espesor	57.945 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE