


## Rodamiento conico

### M241547-M241510-TIMKEN - M241547-M241510-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/m241547-m241510-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |         |         | Load Ratings                          |                         |                                       |                                      |                       |        | Part Number |         |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|--------------------------------------|-----------------------|--------|-------------|---------|
| Bore d             | O.D. D  | Width B | Dynamic <sup>(1)</sup> C <sub>1</sub> | Factor <sup>(2)</sup> e | Dynamic <sup>(1)</sup> C <sub>2</sub> | Factor <sup>(2)</sup> e <sub>2</sub> | Static C <sub>3</sub> | Inner  | Outer       |         |
| mm                 | mm      | mm      | N                                     |                         | N                                     |                                      | N                     |        |             |         |
| 203.200            | 292.100 | 57.945  | 60000                                 | 0.33                    | 15000                                 | 86500                                | 1.76                  | 117000 | M241547     | M241510 |
| 8.0000             | 11.5000 | 2.2613  | 130000                                |                         | 20000                                 | 119000                               |                       | 263000 |             |         |

| Bearing Dimensions |         |                          |  |                                      |  |                                      |                               |                               |                               | Geometry Factors |                |                | Bearing Weight                |                |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|-------------------------------|----------------|
| Shaft              |         |                          |  |                                      | Housing                                    |                                      |                               |                               |                               | Cage             | G <sub>1</sub> | G <sub>2</sub> |                               | C <sub>3</sub> |
| Width B            | Width C | ER. Dr. α <sup>(1)</sup> | Max Shaft Fillet Radius R <sup>(1)</sup> | Backing Shoulder Dia. d <sub>s</sub> | Max Housing Fillet Radius r <sup>(1)</sup> | Backing Shoulder Dia. D <sub>s</sub> | A <sub>1</sub> <sup>(1)</sup> | A <sub>2</sub> <sup>(1)</sup> | A <sub>1</sub> <sup>(2)</sup> |                  |                |                | A <sub>2</sub> <sup>(2)</sup> |                |
| 57.945             | 46.696  | -4.8                     | 3.5                                      | 217.0                                | 221.6                                      | 3.3                                  | 276.0                         | 272.6                         | 4.7                           | 2.8              | 0.541          | 127.9          | 0.1279                        | 12.06          |
| 2.2613             | 1.8125  | -0.19                    | 0.14                                     | 8.54                                 | 8.73                                       | 0.13                                 | 10.66                         | 10.71                         | 0.16                          | 0.09             |                |                |                               | 26.58          |

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | TIMKEN        |
| N° Ean13          | 3663952327129 |
| Diámetro interior | 203.2 mm      |
| Diámetro exterior | 292.1 mm      |
| Espesor           | 57.945 mm     |
| Envasado          | 1             |

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE