


Rodamiento conico

KLL352149-KLL352110-TIMKEN - KLL352149-KLL352110-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/kll352149-kll352110-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|---------------------------------------|-----------------------|--------|-------------|-----------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ C _{2e} | Static C ₃ | Inner | Outer | |
| mm | mm | mm | N | | N | N | N | | | |
| 279.400 | 317.500 | 24.384 | 102000 | 1.73 | 42100 | 24900 | 1.60 | 467000 | KLL352149 | KLL352110 |
| 11.000 | 12.500 | 0.960 | 36500 | | 9400 | 5810 | | 102000 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|------------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|------|
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ⁽¹⁾ | Backing Shoulder Dia. D _s | Cage A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | A ₃ ⁽¹⁾ | G ₁ | G ₂ | C ₃ | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | kg | |
| 24.384 | 19.298 | 20.3 | 1.5 | 296.0 | 208.6 | 1.5 | 312.8 | 300.0 | 1.8 | 2.1 | 1131.2 | 795.2 | 0.1688 | 2.67 |
| 0.960 | 0.720 | 0.80 | 0.06 | 11.26 | 11.34 | 0.06 | 12.28 | 12.17 | 0.07 | 0.09 | | | | 5.89 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| N° Ean13 | 3663952328898 |
| Diámetro interior | 279.4 mm |
| Diámetro interior | 11" inch |
| Diámetro exterior | 317.5 mm |
| Diámetro exterior | 12 1/2" inch |
| Espesor | 24.384 mm |
| Espesor | 0.96" inch |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE