


## Rodamientos a rótula de bola 1212-K-TVH-C3-H212-FAG - 1212-K-TVH-C3-H212-FAG

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/rotula/1212-k-tvh-c3-h212-fag>

**Self-aligning ball bearings 1212-K-TVH-C3 + H212**  
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve



$d_{min}$	55 mm
D	110 mm
B	22 mm
$B_{smin}$	5 mm
c	13 mm
$D_1$	95,8 mm
$D_{smax}$	101 mm
$D_{s1}$	80 mm
d	60 mm
$d_1$	78 mm
$d_{smax}$	68 mm
$d_{smin}$	64 mm
l	39 mm
$F_{smax}$	1,5 mm
$F_{s1}$	H212 Mass, adapter sleeve
m	0,88 kg Mass
m <sub>1</sub>	0,35 kg Mass, adapter sleeve
C	30500 N Basic dynamic load rating, radial
e	0,18
$Y_1$	3,47
$Y_2$	5,37
$C_{10}$	11400 N Basic static load rating, radial
$Y_0$	3,64
$n_0$	6700 1/min Limiting speed
$n_2$	8500 1/min Reference speed
$C_{10}$	710 N Fatigue limit load, radial

### CARACTERÍSTICAS DEL PRODUCTO

Marca	FAG
N° Ean13	3663952346236
Diámetro interior	55 mm
Diámetro exterior	110 mm
Espesor	22 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE