

Rodamiento conico 30221-TIMKEN - 30221-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/30221-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • IsoClass

IsoClass

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|----------------------|-------------|--|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽³⁾ C ₂ | Factor ⁽⁴⁾ K | Static C ₀ | Assembly Inner/Outer | | |
| mm | mm | mm | N | | N | | N | | | |
| in. | in. | in. | lbf | | lbf | | lbf | | | |
| 105.000 | 190.000 | 39.000 | 320000 | 4.52 | 84000 | 1.28 | 407000 | | 30221 | |
| 4.1339 | 7.4803 | 1.5354 | 72000 | | 19000 | | 91400 | | | |

| Mounting Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|---------------------|---------|-------------------------|--|--------------------------------------|--|--------------------------------------|--------------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|------|
| Drift | | | | | Housing | | | | | Cage | | | | |
| Width B | Width C | ER Co. a ⁽¹⁾ | Max Shaft Fillet Radius R ⁽²⁾ | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ⁽³⁾ | Backing Shoulder Dia. D _s | Backing Shoulder Dia. D ₂ | A ₁ ⁽⁴⁾ | A ₂ ⁽⁵⁾ | G ₁ | G ₂ | C ₃ | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | lb. | |
| 36.000 | 36.000 | -1.3 | 3.6 | 100.0 | 126.0 | 2.5 | 176.0 | 102.0 | 4.5 | 1.1 | 180.7 | 98.4 | 3.090 | 4.40 |
| 1.4173 | 1.4173 | -0.05 | 0.12 | 4.72 | 4.98 | 0.10 | 7.05 | 3.77 | 0.18 | 0.05 | | | 0.98 | |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| N° Ean13 | 3663952353913 |
| Diámetro interior | 105 mm |
| Diámetro exterior | 190 mm |
| Espesor | 39 mm |
| Peso | 4470 g |
| Carga dinámica | 325 kN |
| Carga estática | 407 kN |
| Envasado | 1 |
| Estándar | Ninguna norma |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE