


Rodamiento conico 32032X-TIMKEN - 32032X-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/32032x-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • IsoClass

IsoClass



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynami ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynami ⁽³⁾ C ₂	Factor ⁽⁴⁾ K	Static C ₀	Assembly Inner/Outer		
mm	mm	mm	N		N		N			
160.000	240.000	51.000	480000	0.16	1250000	0.16	833000		32032X	
6.3002	9.4488	2.0079	108000		28000		182000			

Mounting Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G ₁	G ₂		C ₃
Width B	Width C	ER Co. a ⁽¹⁾	Max Shaft Fillet Radius R ⁽²⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽³⁾	Backing Shoulder Dia. D _s	Backing Shoulder Dia. D _s	A ₁ ⁽⁴⁾	A ₂ ⁽⁵⁾				G ₁	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
160.000	240.000	1.8	3.0	176.0	181.0	2.5	234.0	221.0	3.5	4.1	501.7	123.9	0.1166	7.85
2.0079	1.4907	0.07	0.12	6.89	7.13	0.10	9.21	8.70	0.13	0.16				12.21

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952354071
Diámetro interior	160 mm
Diámetro exterior	240 mm
Espesor	51 mm
Peso	7750 g
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE