


Casquillos de agujas YB98-IKO - YB98-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/yb98-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
14.288 ($\frac{9}{16}$)	—	—	—	—	—	—	—	—	YB 98 10.1
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	b_2	Shaft dia. h8	Housing bore dia. J7	C	C_0	N	N
14.288	19.050	12.701	500	Max. Min.	Max. Min.	11 600	20 400	11 000	RB 68

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952361604
Diámetro interior	14.288 mm
Diámetro exterior	19.05 mm
Espesor	12.7 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE