

Casquillos de agujas BHAM1612-IKO - BHAM1612-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bham1612-iko>

Shaft dia. mm (inch)	Standard			Closed end			Identification number			Grease retained Mass (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained		
25.400 (1)	—	—	—	—	—	—	—	BHAM 1612	37	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring
F_w	D	C	Shaft dia. d	Housing bore dia. $J7$	Max.	Min.	C	C_0	rpm	
25.400	33.338	19.05	25.400	25.387	33.352	33.327	19 900	29 700	15 000	IRB 1212

Note*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952362014
Diámetro interior	25.4 mm
Diámetro exterior	33.338 mm
Espesor	19.05 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE