

## Casquillos de agujas YB2012-IKO - YB2012-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/yb2012-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
31.750 (1 1/4)	—	—	—	—	—	—	—	—	<b>YB 2012</b> 42.5		
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	$t$	Shaft dia. mm	Housing bore dia. mm	$C$	$C_0$	N	N	rpm	IRB 1612
31.750	38.100	19.05	—	31.750	31.734	38.114	38.089	31 800	72 500	4 500	IRB 1612

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952362342
Diámetro interior	31.75 mm
Diámetro exterior	38.1 mm
Espesor	19.05 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE