


## Rodamiento conico

### EE724121D-724195-TIMKEN - EE724121D-724195-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/ee724121d-724195-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDI

**TYPE TDI**



| Bearing Dimensions |         |         |                           | Load Ratings                          |                                     |                                     |                                     |                                       |                                       |  |                        |      |  |
|--------------------|---------|---------|---------------------------|---------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|---------------------------------------|---------------------------------------|--|------------------------|------|--|
| Bore d             | O.D. D  | Width T | Double Inner Ring Width B | Dynamic <sup>CR</sup> C <sub>10</sub> | Static <sup>CR</sup> C <sub>0</sub> | Factor <sup>CR</sup> Y <sub>1</sub> | Factor <sup>CR</sup> Y <sub>2</sub> | Dynamic <sup>CR</sup> C <sub>90</sub> | Dynamic <sup>CR</sup> C <sub>50</sub> | Dynamic <sup>CR</sup> C <sub>100</sub> | Factor <sup>CR</sup> K |      |  |
| mm                 | mm      | mm      | mm                        | N                                     | N                                   | N                                   | N                                   | N                                     | N                                     | N                                      |                        |      |  |
| 304.800            | 495.300 | 171.450 | 165.100                   | 250000                                | 80000                               | 0.4                                 | 1.7                                 | 2.5                                   | 437000                                | 301000                                 | 202000                 | 1.45 |  |
| 12.000             | 19.500  | 6.700   | 6.5000                    |                                       |                                     |                                     |                                     |                                       | 98300                                 | 67700                                  | 171900                 |      |  |

| Part Number |        | Dimensions                             |                                      |  |                                      | Geometry Factors |                |                | Bearing Weight |
|-------------|--------|--|--------------------------------------|--|--------------------------------------|------------------|----------------|----------------|----------------|
| Inner       | Outer  | Max Shaft Fillet Radius r <sub>s</sub> | Backing Shoulder Dia. d <sub>s</sub> | Max Housing Fillet Radius r <sub>h</sub> | Backing Shoulder Dia. D <sub>s</sub> | G <sub>1</sub>   | G <sub>2</sub> | C <sub>3</sub> | kg             |
| mm          | mm     | mm                                     | mm                                   | mm                                       | mm                                   |                  |                |                | lbs            |
| EE724121D   | 724195 | 3.3                                    | 324.9                                | 6.4                                      | 498.8                                | 2180.9           | 169.7          | 0.1180         | 106.31         |
|             |        | 0.13                                   | 13.15                                | 0.25                                     | 13.72                                |                  |                |                | 236.25         |

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | TIMKEN        |
| N° Ean13          | 3663952370248 |
| Diámetro interior | 304.648 mm    |
| Diámetro exterior | 495.3 mm      |
| Espesor           | 171.45 mm     |
| Envasado          | 1             |

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE