


## Rodamiento de agujas GBRI162816-IKO - GBRI162816-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/gbri162816-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
<b>25.400</b> (1)	<b>GBRI 162816</b>	184	25.400 (1)	44.450 (1) <sub>0</sub>	25.400 (1)	25.650	31.750 (1) <sub>0</sub>

Standard mounting dimensions mm		Ball diam. mm C	Basic dynamic load rating N	Allowable rotational speed (1) rpm	Assembled inner ring		
d <sub>a</sub> Min.	d <sub>a</sub> Max.						
30.5	30.7	39.6	0.6	46 600	83 900	4 500	<b>LRBZ 162016</b>

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952377445
Diámetro interior	25.4 mm
Diámetro exterior	44.45 mm
Espesor	25.65 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE