


## Rodamiento de agujas GBR445628-IKO - GBR445628-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/gbr445628-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			F <sub>d</sub>	D	C	D <sub>s</sub> Max.	r <sub>as</sub> max
<b>69.850</b> (2 3/4)	<b>GBR 445628</b>	690	69.850 <sup>(1)</sup> <sub>0</sub>	88.900 <sup>(1)</sup> <sub>0</sub>	44.450 <sup>(1)</sup> <sub>0</sub>	82	1.5
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
147 000	336 000	2 000					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
2. The outer ring has an oil groove and an oil hole.  
No grease is pre-packed. Perform proper lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952377605
Diámetro interior	69.85 mm
Diámetro exterior	88.9 mm
Espesor	44.45 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE