


Rodamiento de agujas GBR101812-IKO - GBR101812-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/gbr101812-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾)	
			F _d	D	C	D _s Max.	r _{as} max
15.875 (⁽²⁾)	GBR 101812	55.5	15.875 ⁽¹⁾ / ₀	28.575 ⁽¹⁾ / ₀	19.050 ⁽¹⁾ / ₀	24.5	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽³⁾					
N	N	rpm					
23 500	28 500	9 500					

Notes:
(¹) Maximum permissible corner radius of the housing.
(²) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is preapplied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952377698
Diámetro interior	15.875 mm
Diámetro exterior	28.575 mm
Espesor	19.05 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE