


## Rodamiento de agujas GBRI406028-IKO - GBRI406028-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/gbri406028-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
<b>63.500</b> (2 1/2)	<b>GBRI 406028</b>	1 230	63.500 3 <sub>0</sub>	95.250 3 <sub>0</sub>	44.450 1 <sub>0</sub>	44.700	76.200 3
Standard mounting dimensions mm		Ball diam. mm C	Basic load rating N	Limiting load rating N	Allowable rotational speed (1) rpm	Assembled inner ring	
d <sub>a</sub> Min.	d <sub>a</sub> Max.					D <sub>a</sub> Max.	r <sub>as max</sub> (1)
71	73	88	154 000	368 000	2 000	<b>LRBZ 404828</b>	

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952377940
Diámetro interior	63.5 mm
Diámetro exterior	95.25 mm
Espesor	44.45 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE