


## Rodamiento de agujas GBRI446832-IKO - GBRI446832-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/gbri446832-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
<b>69.850</b> (2 3/4)	<b>GBRI 446832</b>	1 840	69.850 (2 3/4)	107.950 (4 1/4)	50.800 (2)	51.050	82.550 (3 1/4)

Standard mounting dimensions mm				Basic dynamic load C <sub>10</sub> (N)	Limiting static load C <sub>0</sub> (N)	Allowable rotational speed (1) (rpm)	Assembled inner ring
d <sub>a</sub> Min.	d <sub>a</sub> Max.	D <sub>a</sub> Max.	r <sub>as max</sub> (1)				
77	79	99.9	1.5	214 000	452 000	1 800	<b>LRBZ 445232</b>

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952377964
Diámetro interior	69.85 mm
Diámetro exterior	107.95 mm
Espesor	50.8 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE