


Rodamiento de agujas RNA4914-U-IKO - RNA4914-U-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/rna4914-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|--|------------------------------------|-------------------------------------|---|---------------|---------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_a (1) |
| 80 | --- | RNA 4914U | --- | --- | 495 | 80 | 100 | 30 | 1 |
| Standard rounding dimension D_s Max. mm | | | | | | | | | |
| | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed (reference speed) rpm | | | | | | |
| | 95 | 76 900 | 143 000 | 2 500 | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| N° Ean13 | 3663952379609 |
| Diámetro interior | 80 mm |
| Diámetro exterior | 100 mm |
| Espesor | 30 mm |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE