

## Rodamiento de agujas NA6913-UU-IKO - NA6913-UU-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/na6913-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
65	—	—	NA 6913UU	—	845	65	90	45	46

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub>	Basic dynamic load rating C	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		Min.	Max.				
1	72	70	70.5	85	97 400	200 000	LRTZ 657246

Notes: (1) Minimum allowable value of shaft dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952381725
Diámetro interior	65 mm
Diámetro exterior	90 mm
Espesor	46 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE