

Rodamiento de agujas
NA4916-U-IKO - NA4916-U-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/na4916-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



NA4916-U
NA4916-U (1/30)

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
80	—	NA 4916U	—	—	860	80	110	30	31

r _s mm	F _N	Standard mounting dimensions mm		Basic rating C	Basic rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
		d _s Min.	d _s Max.					
1	90	85	88	105	80 700	158 000	2 000	LRTZ 809031

Notes⁽¹⁾ Minimum allowable value of shaft diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952381824
Diámetro interior	80 mm
Diámetro exterior	110 mm
Espesor	31 mm
Envasado	1

contacto@123rodamiento.mx
+34 911 436 830
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE