

Rodamiento de agujas NA4917-U-IKO - NA4917-U-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/na4917-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
85	—	NA 4917U	—	—	1 300	85	120	35	36

r _s mm	F _w	Standard mounting dimensions mm		Basic static load rating C ₀	Basic dynamic load rating C ₁₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
		d _s Min.	d _s Max.					D _s Max.
1.1	100	91.5	98	113.5	103 000	225 000	1 900	LRTZ 8510036

Notes:
(1) Minimum allowable value of shaft diameter r.
(2) Allowable rotational speed applies to grease lubrication.
Remark:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952381862
Diámetro interior	85 mm
Diámetro exterior	120 mm
Espesor	36 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE