


Rodamiento de agujas BR324120-U-IKO - BR324120-U-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/br324120-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
50.800 (2)		BR 324120 U	216	50.800 (2)	65.088 (2 3/4)	31.750 (1 1/4)
Standard mounting dimensions mm		Basic dynamic load rating C	Static load rating C_0	Allowable rotational speed ⁽²⁾		
D_1 Max.	r_{as} max (1)	N	N	rpm		
57.8	1.5	51 000	89 400	4 000		

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952382302
Diámetro interior	50.8 mm
Diámetro exterior	65.088 mm
Espesor	31.75 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE