

## Rodamiento de agujas GBR122016-U-IKO - GBR122016-U-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/gbr122016-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>19.050</b> (3/4)	<b>GBR 122016 UU</b>		79	19.050 (3/4)	31.750 (1 1/4)	25.400 (1)
Standard mounting dimensions mm		Ball dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_s$ Max.	$r$ as max ( <sup>(†)</sup> )	N	N	rpm		
27	0.6	26 400	34 500	4 000		

Notes: <sup>(†)</sup> Minimum allowable value of chamfer dimension  $r$ .  
<sup>(\*)</sup> Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952382876
Diámetro interior	19.05 mm
Diámetro exterior	31.75 mm
Espesor	25.4 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE