


Rodamiento de agujas GBRI82016-UU-IKO - GBRI82016-UU-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/gbri82016-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number				Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals		With one seal			d	D	C	
12.700 ($\frac{1}{2}$)	GBRI 82016 UU				110	12.700 ($\frac{1}{2}$)	31.750 ($1\frac{1}{4}$)	25.400 (1)	
		Standard mounting dimensions mm				Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
B	F _w	d ₁ Min.	d ₂ Max.	D _s Max.	r _{as max} ⁽¹⁾				
25.650	19.050 ($\frac{3}{4}$)	17.5	18	27	0.6	26 400	34 500	4 000	LRBZ 81216

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
 Note⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952383309
Diámetro interior	12.7 mm
Diámetro exterior	31.75 mm
Espesor	25.4 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE