


Rodamiento de agujas GBRI183020-U-IKO - GBRI183020-U-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/gbri183020-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	
28.575 (1 1/8)	GBRI 183020 U		240	28.575 (1 1/8)	47.625 (1 7/8)	31.750 (1 1/4)	
		Standoff mounting dimensions - mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
<i>B</i>	<i>F_w</i>	Min.	Max.	<i>D_s</i> Max.	<i>r_{as max}</i> ⁽¹⁾	N	N
32.000	34.925 (1 3/8)	33.5	33.9	42.8	0.6	49 500	91 800
						2 500	LRBZ 182220

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952383385
Diámetro interior	28.575 mm
Diámetro exterior	47.625 mm
Espesor	31.75 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE