

## Rodamiento de agujas GBRI243920-UU-IKO - GBRI243920-UU-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/gbri243920-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
<b>38.100</b> (1 1/2)	<b>GBRI 243920 UU</b>		400	38.100 (1 1/2)	61.912 (2 3/8)	31.750 (1 1/4)

  

B	F <sub>w</sub>	Standoff mounting dimensions - mm			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		Min.	Max.	D <sub>s</sub> Max.				
32.000	47.625 (1 7/8)	43.3	45	56.2	61 100	121 000	1 700	<b>LRBZ 243020</b>

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952383477
Diámetro interior	38.1 mm
Diámetro exterior	61.912 mm
Espesor	31.75 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE