

Rodamiento de agujas NAFW304526-IKO - NAW304526-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/naw304526-iko>

IKO
NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE
With Inner Ring



| Shaft dia. mm | Identification number | Mess (Ref.) g | Boundary dimensions mm | | | | | Standard mounting dimensions mm | | | | |
|----------------------------------|-----------------------------------|---|------------------------|-----|-----|--------------------------|-------|---------------------------------|------------|------------|------------|------|
| | | | d | D | C | r_s min ⁽¹⁾ | F_w | d_b | D_b Max. | d_b Min. | D_b Max. | |
| 30 | NAFW 304526 | 155 | 30 | 45 | 26 | 0.3 | 35 | 39.5 | 43 | 32 | 34 | 35.6 |
| Basic dynamic load rating C | Basic static load rating C_0 | Allowable rotational speed ⁽²⁾ | Assembled roller ring | | | | | | | | | |
| N | N | rpm | LRT 303526 | | | | | | | | | |
| 26 600 | 51 500 | 14 000 | | | | | | | | | | |

Notes:
(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952384597 |
| Diámetro interior | 30 mm |
| Diámetro exterior | 45 mm |
| Espesor | 26 mm |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE