


Rodamiento de agujas TRU10515350-UU-IKO - TRU10515350-UU-IKO


<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/tru10515350-uu-iko>



ROLLER BEARINGS

Caged Roller Bearings With Seal

Full Complement Roller Bearings With Seal



NAU49-UU
TRU-UU

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r ⁽¹⁾ min	J
105	---	TRU 10515350UU		2 890	105	153	50	1.5	120
<i>E_w</i>	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n ₂ rpm						
138	N 159 000	N 286 000	1 600						

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952386621
Diámetro interior	105 mm
Diámetro exterior	153 mm
Espesor	50 mm
Invasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE