


## Rodamiento de agujas NAS5034-ZZ-NR-IKO - NAS5034-ZZ-NR-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/nas5034-zz-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
170		NAS 5034ZZNR	22.5	170	260	270	122	121	99	11
<i>f</i>	<i>c</i>	<i>r</i> mm <sup>(1)</sup>	<i>J</i>	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm				
4	3.5	1.5	204.5	857 000	1 730 000	600				

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension *r*  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAG and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952387116
Diámetro interior	170 mm
Diámetro exterior	260 mm
Espesor	122 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE