


## Rodamiento de agujas NAS5076-UU-IKO - NAS5076-UU-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/nas5076-uu-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



| Shaft dia. mm | Identification number |             | Mass (Ref.) kg | Boundary dimensions mm |     |                |     |     |                |   |
|---------------|-----------------------|-------------|----------------|------------------------|-----|----------------|-----|-----|----------------|---|
|               | Sealed type           | Shield type |                | d                      | D   | D <sub>2</sub> | B   | C   | C <sub>1</sub> | S |
| 380           | NAS 5076UU            |             | 200            | 380                    | 560 | —              | 243 | 241 | —              | — |

| f | c | r <sub>s</sub> mm <sup>(1)</sup> | J   | Basic dynamic load rating C | Static load rating C <sub>0</sub> | Allowable rotational speed <sup>(2)</sup> |
|---|---|----------------------------------|-----|-----------------------------|-----------------------------------|---|
|   |   |                                  |     | N                           | N                                 | rpm                                       |
| — | 6 | 2.5                              | 442 | 3 580 000                   | 8 300 000                         | 250                                       |

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| N° Ean13          | 3663952387352 |
| Diámetro interior | 380 mm        |
| Diámetro exterior | 560 mm        |
| Espesor           | 243 mm        |
| Envasado          | 1             |

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE