


Rodamiento de agujas NBXI1730-IKO - NBXI1730-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/nbxi1730-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



Shaft dia. mm	Identification number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
17	---	---	NBXI 1730			108	17	30	35

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 172020	
D ₂	L	B	H	I ₁	r ⁽¹⁾	r _{max}	r _{min}	d ₄	d ₅		Radial	Axial			Radial
36	30	20.5	10	10.5	0.3	0.3	20	33	19	17 600	19 000	25 400	48 700	11 000	

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remark 1: The outer ring has an oil groove and an oil hole.
 2: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952390789
Diámetro interior	17 mm
Diámetro exterior	30 mm
Espesor	30 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE