


Rodamiento de agujas NAXI3532-IKO - NAXI3532-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/naxi3532-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



Shaft dia. mm	Identification number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
35	NAXI 3532	265	—	—	—	—	35	52	60

Boundary dimensions mm			r ⁽¹⁾	r _{max} ⁽²⁾	r _{min} ⁽²⁾	d ₄	d ₅	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽³⁾ rpm	Assembled inner ring LRT 354020			
D ₂	L	H						Radial	Axial	Radial	Axial					
61	32	20	13	10	0.6	0.3	40	52	39	29	400	26 900	54 100	50 000	5 500	LRT 354020

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remark 1: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952390925
Diámetro interior	35 mm
Diámetro exterior	52 mm
Espesor	32 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE