


Rodamiento de agujas NAXI4535-IKO - NAXI4535-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/naxi4535-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
45	NAXI 4535	358	—	—	—	—	45	62	70

Boundary dimensions mm			r ⁽¹⁾	r _{max} ⁽²⁾	r _{min} ⁽²⁾	d ₄	d ₅	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽³⁾ rpm	Assembled inner ring LRT 455025			
D ₂	L	B						Radial	Axial	Radial	Axial					
71.5	35	25	14	10	0.6	0.3	50	62	49	42	200	28 800	83 400	60 100	4 500	LRT 455025

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952391007
Diámetro interior	45 mm
Diámetro interior	1.772" inch
Diámetro exterior	62 mm
Diámetro exterior	2.441" inch
Espesor	35 mm
Espesor	1.378" inch
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE