


Rotulas GE SB11518098-IKO - SB11518098-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/ge/sb11518098-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree α
	SB	11518098		d	D	B	C	d_k	r_1 mm	
115	SB	11518098	10.3	115	180	98	85	165	1	5
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s						
d_a	D_a	C_d	C_s							
Min. Max. ⁽²⁾	Min.	N	N							
120.5 132.5	174.5 152	1 380 000	8 250 000							

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_a .
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952391571
Diámetro interior	115 mm
Diámetro exterior	180 mm
Espesor	98 mm
Tipo	GE
Lubricación	sin
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE