

Rotulas GE SB150A-IKO - SB150A-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/ge/sb150a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree α	
			d	D	B	C	d_k ⁽¹⁾ r_s mm		
150	SB 150A	17.0	150	220	120	105	205	1	5
Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N						
d_s Min.	d_s Max. ⁽²⁾			D_s Min.	D_s Max.				
155.5	166	2 110 000	12 700 000	214.5	189				

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952391625
Diámetro interior	150 mm
Diámetro exterior	220 mm
Espesor	120 mm
Tipo	GE
Lubricación	sin
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE