


Rotulas GE SB150220120-IKO - SB150220120-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/ge/sb150220120-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | Permissible tilting angle degree | |
|---------------------------|-----------------------|--------------------------------|-------------------|-------------------------------|-----|-------|-------|-------|-------------------------------------|---|
| | d | D | | B | C | d_k | r_1 | r_2 | | |
| 150 | SB 150220120 | | 17.0 | 150 | 220 | 120 | 105 | 205 | 1 | 5 |
| Mounting dimensions mm | | Dynamic load capacity C_d | | Static load capacity C_s | | | | | | |
| d_s | D_s | C_d | C_s | | | | | | | |
| Min. Max. ⁽²⁾ | Min. Max. | N | N | | | | | | | |
| 155.5 166 | 214.5 189 | 2 110 000 | 12 700 000 | | | | | | | |

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| N° Ean13 | 3663952391632 |
| Diámetro interior | 150 mm |
| Diámetro exterior | 220 mm |
| Espesor | 120 mm |
| Tipo | GE |
| Lubricación | sin |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE