


## Rodamiento conico 32956-JR-JTEKT - 32956-JR-KOYO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/32956-jr-koyo>

Single-row tapered roller bearings  
metric series Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.					
<b>280</b>	380	63.5	63.5	48	780	1630	770	1000	<b>32956JR</b>				
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors (Refer. 1)		Mass (kg)
4EC	75.1	d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.	0.43	Y <sub>1</sub>	Y <sub>0</sub>	20.14
		294	298	368	347	368	11	15.5	2.5	2	1.39	0.76	

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250125812
Diámetro interior	280 mm
Diámetro exterior	380 mm
Espesor	63.5 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE