

Rodamiento conico 32926-JR-JTEKT - 32926-JR-KOYO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/32926-jr-koyo>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 130 | 180 | 32 | 32 | 25 | 2 | 1.5 | 200 | 368 | 1 900 | 2 500 | 32926JR | | | |
| Dimension series to ISO 995 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| 20C | 31.4 | 140 | 141 | 171 | 165 | 174 | 6 | 7 | 2 | 1.5 | 0.34 | 1.77 | 0.97 | 2.42 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 4549250125669 |
| Diámetro interior | 130 mm |
| Diámetro exterior | 180 mm |
| Espesor | 32 mm |
| Envasado | 1 |
| Estándar | Ninguna norma |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE