


Seguidor de leva CFE12-VBUU-IKO - CFE12-VBUU-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe12-vbuu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)							
	Shield type			Sealed type			Ø	D	C	d _e				
16	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 12	VBUU					107	30	14	16
Boundary dimensions mm														
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	H	f _{max}	f	Mounting dimension mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	6	0.6/0.8	21	21.9	13 500	19 700	13 200

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3616060460486
Diámetro interior	16 mm
Diámetro exterior	30 mm
Espesor	14 mm
Peso	107 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE