


Seguidor de leva CFE20-VBUU-IKO - CFE20-VBUU-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe20-vbuu-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Hexagon Hole**



CFE-VBUU

| Outside diameter of eccentric collar mm | Identification number | | | | | | Mass (Ref.) | | | | | | | | |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|----------------|----------------|-------------|----------|-----------------|--|-------------------------------------|---|------------------------------------|--------|--------|
| | Shield type | | | Sealed type | | | g | D | C | d _e | | | | | |
| 27 | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | CFE 20 | VBUU | 505 | 52 | 24 | 27 | | | | | |
| Boundary dimensions mm | | | | | | | | | | | | | | | |
| G | B ₃ | B ₁ max | B ₂ max | B ₂ | C ₁ | G ₁ | H | (°) face | f Min. mm | Mounting dimension Maximun splining torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N | | |
| M20 X 1.5 | 19.5 | 25.6 | 66.1 | 40.5 | 0.8 | 8 | 21 | 8 | 1 | 0.8 | 34 | 119 | 33 200 | 64 500 | 37 500 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| N° Ean13 | 3616060460639 |
| Diámetro interior | 27 mm |
| Diámetro exterior | 52 mm |
| Espesor | 24 mm |
| Peso | 505 g |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE