


Seguidor de leva CFE30-VBUU-IKO - CFE30-VBUU-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe30-vbuu-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

| Outside diameter of eccentric collar mm | Identification number | | | | | | Mass (Ref.) | | | |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|---------------|-------------|-------------|----|----|----------------|
| | Shield type | | | Sealed type | | | Ø | D | C | d _e |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | | | |
| 41 | | | | | CFE 30 | VBUU | 2 030 | 80 | 35 | 41 |

| Boundary dimensions mm | | | | | | | | | | | | | | | |
|------------------------|----------------|-----------------------|-----------------------|----------------|----------------|---|----------|-------------------|---------------------------------------|--------------------------------|-------------------------------------|---|------------------------------------|---------|--------|
| G | B ₃ | B ₁ max | B ₂ max | C ₁ | G ₁ | H | (°) base | Eccentricity g | Mounting dimension f Min. mm | Maximum splining torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N | | |
| M30×1.5 | 32.5 | 37 | 100 | 63 | 1 | 8 | 30.5 | 17 | 1 | 1.5 | 49 | 438 | 67 700 | 144 000 | 85 900 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| N° Ean13 | 3616060460790 |
| Diámetro interior | 41 mm |
| Diámetro exterior | 80 mm |
| Espesor | 35 mm |
| Peso | 2030 g |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE