

## Seguidor de leva CR16-VBR-IKO - CR16-VBR-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr16-vbr-iko>

**IKO**  
**CAM FOLLOWERS**  
Inch Series Cam Followers **With Cage/With Screwdriver Slot**

Stud dia. mm (inch)	Identification number		Shield type With cover With cylindrical outer ring	Sleeve type With cylindrical outer ring	Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	CR 16	VBR									
11.112 ( $\frac{7}{16}$ )	CR 16	VBR			74	25.400 ( $\frac{1}{16}$ )	15.875 ( $\frac{5}{8}$ )	11.112 ( $\frac{7}{16}$ )	$\frac{1}{2}$ -20	12.700 ( $\frac{1}{2}$ )	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
17.3 (0.68)	25.400 ( $\frac{1}{16}$ )	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{16}$ )	4.782 ( $\frac{3}{16}$ )	3.175 ( $\frac{1}{8}$ )	6.350 ( $\frac{1}{4}$ )	1.191 ( $\frac{1}{16}$ )	17.859 ( $\frac{3}{4}$ )	17.4	13 100	22 700

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3616060463586
Diámetro interior	11.112 mm
Diámetro exterior	25.4 mm
Espesor	15.875 mm
Peso	74 g
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE