


Rodamiento rodillos NA4907UU-JTEKT - NA4907UU-KOYO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/na4907uu-koyo>

Machined ring needle roller bearings 
F_W 29 – 37 mm
With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
F _w	d	D	B	B ₁	C _r	C _{0r}	Oil lub.	Without inner ring		
42	35	55	20	21	0.6	29.0	40.9	4 700	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
With inner ring				d ₂ max.	D ₂ max.	Without inner ring	With inner ring			
NA4907UU				39	51	0.6	—	0.173	IRM354221	

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952483108
Diámetro interior	35 mm
Diámetro exterior	55 mm
Espesor	20 mm
Peso	173 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE