

Rotulas SI DSIL5-T-K-DURBAL - SIL5-T-K-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/sil5-t-k-durbal>

DSIL5-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	measurement (mm)							
DSIL 5 T/K			d	G	B	C ₁	d ₂	d ₃	d ₄	
			5	M 5	8	6,00	18	8,5	11	

type	measurement (mm)			h	d ₁	load rating C ₀ (N)	weight (kg)
	l ₁ min	W					
DSI / DSIL 5 T/K	10	9	27	13	6,0	0,016	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952489070
Diámetro interior	5 mm
Diámetro exterior	18 mm
Espesor	8 mm
Tipo	SI
Peso	16 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE