

Rotulas SI SI30-T-K-DURBAL - SI30-T-K-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/si30-t-k-durbal>


SI30-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 30 TIK		30	M 30 x 2	37	25,00	70	40,0	50

type	measurement [mm]			d ₁	load rating C ₁₀ [kN]	weight [kg]
	l ₁ min	W	h			
SI / SIL 30 TIK	51	41	110	17	114,0	1,100

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952489698
Diámetro interior	30 mm
Diámetro exterior	70 mm
Espesor	37 mm
Tipo	SI
Peso	1100 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE