

## Rotulas SI SI30-T-K-DURBAL - SI30-T-K-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/si30-t-k-durbal>


### SI30-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	
SI 30 TIK		30	M 30 x 2	37	25,00	70	40,0	50	

type	measurement [mm]			d <sub>1</sub>	load rating C <sub>10</sub> [N]	weight [kg]
	l <sub>1</sub> min	W	h			
SI / SIL 30 TIK	51	41	110	17	114,0	1,100

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952489698
Diámetro interior	30 mm
Diámetro interior	1.181" inch
Diámetro exterior	70 mm
Diámetro exterior	2.756" inch
Espesor	37 mm
Espesor	1.457" inch
Tipo	SI
Peso	1100 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE